

**KANO LABORATORIES, INC.  
SAFETY DATA SHEET**

**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:** Pyrolube  
**Product Use:** Lubricant for Industrial Use

**Manufacturer:** Kano Laboratories, LLC  
1000 E. Thompson Lane  
Nashville, TN 37211  
**Information Phone Number:** (615) 833-4101  
**Fax:** (615) 833-5790  
**Website:** www.kroil.com

**SDS Date of Preparation:** February 22, 2021

**SECTION 2: HAZARDS IDENTIFICATION**

**GHS / HAZCOM 2012 Classification:**

<b>Health</b>	<b>Physical</b>
Skin Irritation Category 2 Specific Target Organ Toxicity – Single Exposure Category 3 (CNS) Aspiration Hazard Category 1	Flammable Liquid Category 4

Label Elements

**Danger!**



Combustible Liquid.  
Causes skin irritation.  
May be fatal if swallowed and enters airways.  
May cause drowsiness or dizziness.

Keep away from flames and hot surfaces. No smoking.  
Avoid breathing mist, vapors or spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves, eye protection and face protection.  
IF SWALLOWED: Immediately call a POISON CENTER.  
Do NOT induce vomiting.  
IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation occurs: Get medical attention.  
Take off contaminated clothing and wash it before reuse.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER if you feel unwell.  
In case of fire: Use carbon dioxide, dry chemical or foam to extinguish.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents and container in accordance with local and national regulations.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	%
Aliphatic Hydrocarbons	64742-47-8	60-90
Graphite	778212-4	0.5-5%

### SECTION 4: FIRST AID MEASURES

**Eye:** Rinse thoroughly with water for several minutes, holding the eye lids open to be sure the material is washed out. Get medical attention if irritation develops or persists.

**Skin:** Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use.

**Inhalation:** Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention if symptoms develop.

**Ingestion:** Rinse mouth with water. Do NOT induce vomiting. Keep the victim calm and warm. Never give anything by mouth to an unconscious or drowsy person. Get immediate medical attention.

**Most important symptoms and effects, acute and delayed:** May cause mild eye irritation. Causes skin irritation. Inhalation of vapors or mist may cause upper respiratory tract irritation and central nervous system effects such as headache, dizziness, nausea and vomiting. Harmful or fatal if swallowed. Aspiration into the lungs during ingestion or vomiting may cause lung damage.

**Indication of immediate medical attention and special treatment, if needed:** If swallowed, get immediate medical attention.

### SECTION 5: FIRE FIGHTING MEASURES

**Suitable (and Unsuitable) Extinguishing Media:** Use carbon dioxide, dry chemical or foam. Water may be ineffective but can be used to cool containers and structures.

**Specific Hazards Arising from the Chemical:** Combustible liquid. Liquid and vapors can ignite if exposed to open flames or ignition sources. Never use welding or cutting torch on or near containers (even empty) because product can ignite. Combustion may produce carbon oxides, aluminum oxides, smoke and fumes.

**Special Protective Equipment and Precautions for Fire-fighters:** Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

**Personal precautions, Protective equipment, and Emergency procedures:** Wear appropriate protective clothing to avoid eye and skin contact including impervious gloves, safety goggles and respirator if needed. Ventilate area. Remove all ignition sources such as open flames, spark producing equipment, pilot lights, etc.

**Environmental precautions:** Avoid release to the environment. Report spills and releases as required to appropriate authorities.

**Methods and Materials for Containment and Cleaning up:** Cover with an inert absorbent material and collect into an appropriate container for disposal.

**SECTION 7: HANDLING AND STORAGE**

**Precautions for Safe Handling:** Avoid breathing vapors, aerosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Wash exposed skin thoroughly with soap and water after use. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas.

**OTHER PRECAUTIONS:** Do not cut, braze, solder, grind or weld empty containers. Do not reuse containers. Follow all SDS precautions in handling empty containers.

**Conditions for Safe Storage, Including any Incompatibilities:** Store in a cool, dry, well-ventilated location away from oxidizing agents and other incompatible materials. Keep containers closed.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

Chemical Name	Exposure Limits
Aliphatic Hydrocarbons	525 mg/m <sup>3</sup> TWA Manufacturer
Graphite	5 mg/m <sup>3</sup> TWA (respirable), 15 mg/m <sup>3</sup> TWA (total dust) OSHA PEL 2 mg/m <sup>3</sup> TWA ACGIH TLV (respirable)

**Appropriate Engineering Controls:** Use with adequate general or local exhaust ventilation to maintain concentrations below the occupational exposure limits.

**Personal Protective Equipment:**

**Respiratory Protection:** If needed, a NIOSH approved respirator with organic vapor cartridges may be used. For higher exposures, a supplied air respirator may be required. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

**Hand protection:** Impervious gloves are recommended when needed to avoid skin contact. Based on available test data, neoprene or nitrile gloves are suggested.

**Eye Protection:** Follow facility requirements.

**Skin Protection:** Impervious clothing as required to avoid skin contact and contamination of personal clothing.

**Hygiene measures:** Suitable eye wash and washing facilities should be available in the work area.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b>	Gray liquid	<b>Odor:</b>	Solvent
<b>Odor Threshold:</b>	Not available	<b>pH:</b>	Not applicable
<b>Melting/Freezing Point:</b>	Not available	<b>Boiling Point/Range:</b>	416-449°F (213-232°C)
<b>Flash Point:</b>	174°F (79°C) TAG	<b>Evaporation Rate:</b>	
		<b>(ether=1):</b>	<1
<b>Flammability: (Solid, Gas)</b>	Not applicable	<b>Flammability Limits:</b>	UEL: 7.0% LEL: 0.6%
<b>Vapor Pressure:</b>	<1 @ 20°C	<b>Vapor Density:</b>	>1
<b>Relative Density:</b>	0.77	<b>Solubilities:</b>	Insoluble in Water
<b>Partition Coefficient:</b>	Not available	<b>Autoignition</b>	
<b>(N-Octanol/Water)</b>		<b>Temperature:</b>	448°F (231°C)
<b>Decomposition</b>		<b>Viscosity:</b>	< 20.5 mm <sup>2</sup> /sec @ 40°C
<b>Temperature:</b>	Not available		

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** None known.

**Chemical Stability:** Stable under normal conditions of storage or use.

**Possibility of Hazardous Reactions:** None known.

**Conditions to avoid:** Avoid heat, sparks, flames and sources of ignition.

**Incompatible Materials:** Avoid strong oxidizing agents.

**Hazardous decomposition products:** Combustion will produce carbon oxides, aluminum oxides smoke and fumes.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Potential Health Effects:

**Eye:** May cause mild eye irritation with redness, tearing and stinging.

**Skin:** Cause irritation with redness and swelling. Prolonged or repeated contact may result in defatting and dermatitis.

**Inhalation:** Inhalation of vapors or mists may cause mucous membrane and upper respiratory tract irritation and central nervous system depression. Symptoms may include coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea, fatigue and unconsciousness.

**Ingestion:** Swallowing may cause gastrointestinal irritation with abdominal pain, nausea, vomiting and diarrhea and central nervous system depression with symptoms including headache, dizziness, intoxication, weakness, nausea, and vomiting. Aspiration into the lungs during ingestion or vomiting may cause lung damage.

**Chronic Hazards:** None known.

**Carcinogen Status:** None of the components of this product at greater than 0.1% are listed as carcinogens by OSHA, IARC or NTP.

**Acute toxicity:** Toxicological testing has not been performed on this product as a mixture.

Acute Toxicity Estimate: Oral >2000 mg/kg, Inhalation >7.04 mg/kg, Dermal >5000 mg/kg

Aliphatic Hydrocarbons: Oral rat LD50 > 5000 mg/kg; Dermal rat LD50 > 2000-4000 mg/kg

Inhalation rat LC50 > 6.8 mg/L/4 hr.

Graphite: Oral rat LD50 >2000 mg/kg, Inhalation rat LC50 >2.0 mg/L/4 hr (no mortalities)

## SECTION 12: ECOLOGICAL INFORMATION

**Ecotoxicity:** No toxicity data available for the product.

Aliphatic Hydrocarbons: Not toxic to aquatic organisms (fish, daphnia, algae) up to water solubility.

Graphite: 96 hr LC50 Danio rerio >100 mg/L, 48 hr EC50 daphnia magna >100 mg/L,

72 hr EC50 Pseudokirchnerella subcapitata >100 mg/L

**Persistence and Degradability:** Aliphatic hydrocarbons: Readily biodegradable.

**Bioaccumulative Potential:** Aliphatic hydrocarbons have the potential to bioaccumulate.

**Mobility in Soil:** No data available.

**Other Adverse Effects:** None known

## SECTION 13: DISPOSAL INFORMATION

**Disposal instructions:** Dispose of product in accordance with all local, state/provincial and federal regulations.

**Contaminated packaging:** Offer rinsed packaging material to local recycling facilities.

**SECTION 14: TRANSPORT INFORMATION**

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
<b>DOT (in containers &lt;119 gallons)</b>		Excepted from Hazmat			
<b>DOT (in containers &gt;119 gallons)</b>	NA1993	Combustible liquid, n.o.s. (Petroleum Distillates)	3	PGIII	None
<b>IMDG</b>		Not regulated			
<b>IATA</b>		Not regulated			

**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable – product is transported only in packaged form.

**Special precautions:** None known.

**SECTION 15: REGULATORY INFORMATION**

**U.S. FEDERAL REGULATIONS:**

**CERCLA 103 Reportable Quantity:** This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**SARA TITLE III:**

**Hazard Category for Section 311/312:** Classified as per OSHA GHS classification in Section 2 of this SDS.

**Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

**Section 302 Extremely Hazardous Substances (TPQ):** None

**EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory.

**SECTION 16: OTHER INFORMATION**

**HMIS Ratings:** Health - 2                      Flammability - 2                      Reactivity - 0  
**NFPA Ratings:** Health - 1                      Flammability - 2                      Reactivity - 0

**SDS Revision History:** New formulation – all sections revised.

**Date of preparation:** February 22, 2021

**Date of last revision:** July 31, 2015

The information contained herein has been developed based upon current available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or the consequences of its use or misuse.